

# **STAR TRAC®** **8 SERIES**

The Star Trac 8 Series line was built to give you the quality and performance you expect from high-end machines with user-focused features like dual personal fans, a hot bar with heart rate monitoring and Soft Trac® technology. For a premium experience pair any 8 Series machine with the OpenHub console which provides entertainment, fitness tracking and asset management solutions that will offer a complete fitness experience to facility owners and their members.



## 8-TRX TREADMILL

BASE FEATURES	
DECK SYSTEM	Reversible MDF deck with phenolic coating
RUNNING BELT SYSTEM	22in (55cm) wide belt
SIZE OF RUNNING SURFACE	60in x 22in (152cm x 55cm)
ABSORPTION SYSTEM	Triple cell cushioning system provides maximum shock absorption making the entire deck a sweet spot
STEP UP HEIGHT	10in (25cm)
INCLINE RANGE	0-20% max incline
SPEED RANGE	0.5-15mph (0.5-24kmh)
HEART RATE MEASUREMENT SYSTEM	Telemetry and contact HR, Bluetooth w/19" display option
CENTER CONTROLS BAR	Easily accessible Hot Bar® is located closer to the user with one-finger speed and elevation controls, integrated stop button and contact heart rate grips
DISPLAY	Choose from LCD, 10" or 19" OpenHub display options
USER DETECT SYSTEM	Yes, programmable on/off
ACCESSORIES	Multiple bottle and accessory holders, LCD and 10" displays pre-wired for 8 Series PVS entertainment, 800/900MHz receivers, and tablet holder
MAX USER WEIGHT	500lb (227kg)
DRIVE SYSTEM	5 HP AC motor
ELECTRICAL REQUIREMENTS	110V/20 Amp dedicated circuit with NEMA 5-20 outlet; or 220V/15 Amp dedicated circuit with NEMA 6-15 outlet
ADDITIONAL FEATURES	3.5in rollers

FRAME	
MATERIAL	Powder Coated Aluminum Frame
CUSTOMIZABLE	Paint color options approval required
STANDARD COLOR OPTIONS	Star Trac Silver
LENGTH	85in (215cm)
WIDTH	36in (91cm)
HEIGHT	63in (160cm)
PRODUCT WEIGHT	388lbs (176kg)
SHIPPING DIMENSIONS	86in x 39in x 31in (218cm x 98cm x 80cm)
SHIPPING WEIGHT	470lbs (213kg)

## ADDITIONAL SKUS

9-4080-4CT-10IN-60BLK, 9-9252-8TRX-220UL-19-ISDB-DMB-PAL, 9-9254-8TRX-220CE-19-ISDB-DMB-PAL, 9-9252-8TRX-220UL-19-ATSC, 9-9251-8TRX-110-LCDQ, 9-9251-8TRX-110-LCDQ-KM, 9-9254-8TRX-220CE-LCDQ-KM, 9-9254-8TRX-220CE-LCDQ-MI, 9-9252-8TRX-220UL-LCDQ, 9-9252-8TRX-220UL-LCDQ-KM, 9-9251-8TRX-110-10, 9-9254-8TRX-220CE-10 9-9294-8TRX-220-19-ATSC 9-9294-8TRX-220-PAL 9-9294-8TRX-220-LCDQ-KM 9-9294-8TRX-220-LCDQ-MI